

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 9/19/2023 Version: 1.0

#### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Trade name : ZAP PT22 POLY-ZAP 1/2OZ (144)

Product code : 11730049\_PT22

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, sealants Recommended use : Adhesives, sealants

#### 1.3. Supplier

#### Manufacturer

Pacer Technology

3281 E. Guasti Road, Ste 260, Ontario, CA 91761 USA

California USA

T (909) 987-0550

Regulatory@supergluecorporation.com

# 1.4. Emergency telephone number

Emergency number : 800-424-9300

Emergency 24 hours: (800) 424-9300 (CHEMTREC)

# SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 4

Skin corrosion/irritation Category 2

H315

Serious eye damage/eye irritation Category 2

H319

Causes skin irritation

Causes serious eye irritation

Specific target organ toxicity – Single exposure, Category 3,

H335

May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

# 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)

Precautionary statements (GHS US)

**(!)** 

Signal word (GHS US) : Warning

Hazard statements (GHS US) : H227 - Combustible liquid

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.



# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

# **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	Conc.
ethyl 2-cyanoacrylate		CAS-No.: 7085-85-0	70 – 100
Polymethyl Methacrylate		CAS-No.: 9011-14-7	10 – 30
Hydroquinone		CAS-No.: 123-31-9	< 0.1

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation.

9/19/2023 (Issue date) US - en 2/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

# 5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

# 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

# 6.4. Reference to other sections

For further information refer to section 13.

9/19/2023 (Issue date) US - en 3/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid

breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Packaging materials : Store always product in container of same material as original container.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

ethyl 2-cyanoacrylate (7085-85-0)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Ethyl cyanoacrylate		
ACGIH OEL TWA	0.2 ppm		
ACGIH OEL STEL	CGIH OEL STEL 1 ppm		
Remark (ACGIH)	TLV® Basis: Eye & URT irr; asthma. Notations: DSEN; RSEN		
Regulatory reference ACGIH 2023			
Monitoring methods			
Monitoring methods  Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.			

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment.

#### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Avoid all unnecessary exposure. Wear recommended personal protective equipment. Ocular shower with suitable liquid.

#### Hand protection:

Wear protective gloves: Antistatic gloves

#### Eye protection:

Wear eye protection: Chemical goggles or safety glasses

# Skin and body protection:

Wear protective clothing: Antistatic clothing, Flame retardant protective clothing

9/19/2023 (Issue date) US - en 4/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Respiratory protection:

Wear approved mask

# Personal protective equipment symbol(s):











#### Other information:

PPE compliant with the recommended standards should be selected.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Colorless
Odor : Irritating

Odor threshold : No data available pH : No data available

Melting point : -22 °C Freezing point : No data available

Boiling point : > 200 °C

Flash point : 80 – 93.4 °C

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Not applicable.

Vapor pressure : 0.2 mm Hg

Relative vapor density at  $20^{\circ}$ C :  $\approx 3$ 

Relative density : 1.07 g/mL at 25°C

Density : 1.1 g/cm<sup>3</sup>

Solubility : Polymerizes in water.
Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : 485 °C

Decomposition temperature : No data available Viscosity, kinematic : No data available

Viscosity, dynamic : 80 to 120 Centipoise at 22°C (72°F)

Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

#### 9.2. Other information

VOC content : < 2 (<) %

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

9/19/2023 (Issue date) US - en 5/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong alkalis. Oxidation agents.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

11.	1.	Inf	orn	nati	on	on	toxi	col	ogi	cal	eff	ect	S
				,									

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

E40 agnesive	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

ethyl 2-cyanoacrylate (7085-85-0)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

	`	• ,
LC50 Inhalation - Rat	< 21.1 mg/l	

Нν	,droc	uino	ne (1	23-3	21_9)
	vui ot	IUIIU		20-	וכ-וו

- 1		
	ATE US (oral)	500 mg/kg body weight
	01: " " "	

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Dolumothul	Methacrylate (	(0.0444447)
POIVIIIeurvi	welliativiale	190   I-14-/ I

IARC group 3 - Not classifiable

# Hydroquinone (123-31-9)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

### ethyl 2-cyanoacrylate (7085-85-0)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

9/19/2023 (Issue date) US - en 6/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : None under normal conditions.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

# 12.2. Persistence and degradability

40 adhesive				
Persistence and degradability	Rapidly degradable			
ethyl 2-cyanoacrylate (7085-85-0)				
Persistence and degradability Rapidly degradable				
Polymethyl Methacrylate (9011-14-7)				
Persistence and degradability	Rapidly degradable			
Hydroquinone (123-31-9)				
Persistence and degradability	Rapidly degradable			

# 12.3. Bioaccumulative potential

ethyl 2-cyanoacrylate (7085-85-0)		
Partition coefficient n-octanol/water (Log Pow)	1.42	

# 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

- Disposal must be done according to official regulation

Additional information : Do not re-use empty containers.

# **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

# 14.1. UN number

DOT NA No : NA1993 UN-No. (TDG) : UN1993 UN-No. (IMDG) : Not regulated UN-No. (IATA) : 3334

9/19/2023 (Issue date) US - en 7/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
Proper Shipping Name (TDG) : FLAMMABLE LIQUID, N.O.S.

Proper Shipping Name (IMDG) : Not regulated

Proper Shipping Name (IATA) : Aviation regulated liquid, n.o.s.

# 14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Combustible liquid

TDG

Transport hazard class(es) (TDG) : 3 Hazard labels (TDG) : 3



**IMDG** 

Transport hazard class(es) (IMDG) : Not regulated

**IATA** 

Transport hazard class(es) (IATA) : 9
Hazard labels (IATA) : 9



#### 14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III

Packing group (IMDG) : Not regulated

Packing group (IATA) : III

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

DOT

UN-No.(DOT) : NA1993

DOT Special Provisions (49 CFR 172.102) : 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner

packaging may be increased to 5 L (1.3 gallons).

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

9/19/2023 (Issue date) US - en 8/10

# Safety Data Sheet

**DOT Vessel Stowage Location** 

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

passenger vessel.

: 220 L

**TDG** 

UN-No. (TDG) : UN1993

**TDG Special Provisions** : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly

contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a)UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b)UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c)UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d)UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e)UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a)UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b)UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306,150 - An emergency response assistance plan (ERAP) is required for these dangerous goods under subsection 7.1(6) of Part 7

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

(Emergency Response Assistance Plan).

**Explosive Limit and Limited Quantity Index** 

Excepted quantities (TDG) Passenger Carrying Road Vehicle or Passenger

Carrying Railway Vehicle Index

: 5 L : E1 : 60 L

# **IMDG**

Not regulated

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) Y964 PCA limited quantity max net quantity (IATA) 30kgG PCA packing instructions (IATA) 964 PCA max net quantity (IATA) 450L CAO packing instructions (IATA) 964 : 450L CAO max net quantity (IATA) Special provision (IATA) : A27 ERG code (IATA) : 9A

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

9/19/2023 (Issue date) US - en 9/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Polymethyl Methacrylate	CAS-No. 9011-14-7	10 – 30%
-------------------------	-------------------	----------

Hydroquinone (123-31-9)		
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	100 lb	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form	

# 15.2. International regulations

#### CANADA

# ethyl 2-cyanoacrylate (7085-85-0)

Listed on the Canadian DSL (Domestic Substances List)

#### **Hydroquinone (123-31-9)**

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

# **National regulations**

#### ethyl 2-cyanoacrylate (7085-85-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# Hydroquinone (123-31-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of	H-phrases	Chemical <sup>™</sup>
H227	Combustible liquid	Concepts
H315	Causes skin irritation	Our expertise is your solution.
H319	Causes serious eye irritation	chemical-concepts.com
H335	May cause respiratory irritation	800.220.1966

Safety Data Sheet (SDS), USA

410 Pike Road • Huntingdon Valley, PA 19006

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.